Landfill Drainage

Capping Steep Slopes, Pozidrain G, Silent Valley Landfill, Ebbw Vale, UK





Project Description

Silent Valley, which runs up from the Welsh town of Ebbw Vale, is being restored and turned into a nature reserve managed by the Blaenau Gwent County Council and Gwent Wildlife Trust. The once post-industrial mining valley, contaminated with metal recovery waste has been cleaned up and the upper valley turned into a modern domestic landfill facility which is capped off and landscaped to become part of the nature reserve. Silent Valley is now one of the most beautiful natural environments in Gwent.

The Challenge


With the finished landfill profiles incorporating 80m long 1 in 2.5 slopes the challenge was to achieve a stable cap without any reprofiling or use of geogrid reinforcement. The aim was to install a multi-layered synthetic cap comprising a 1mm LLDPE textured geomembrane with a drainage capability above the membrane and a gas venting capability below.

The challenge was to provide sufficient drainage capacity on both interfaces and adequate interface shear strength to withstand the dead load of the 0.5m cover soil and live load of the construction traffic whilst placing the backfill material on this critical slope.

The required slope stability was not possible to achieve with standard geocomposites typically used for the landfill cap drainage. A geocomposite with enhanced performance was required for this 1 in 2.5 slope application.

Project Information

Client	Silent Valley Waste Ltd
Contractor	Jim Davies Civil Engineering
Consultant	Arup
Products	Pozidrain G7SD surface water drain and Pozidrain G4SD gas drain
Quantity	65,000m ² & 60,000m ² respectively
Benefits	Enhanced frictionHigh flow capacity in both directionsMembrane protection



ABG Pozidrain G
Geocomposite with enhanced frictional properties specifically designed for steep slope installations above and below a capping liner

Landfill Drainage

Capping Steep Slopes, Pozidrain G, Silent Valley Landfill, Ebbw Vale, UK





The Solution

The unique **Pozidrain G** geocomposite was used to provide drainage, gas venting and membrane protection. **Pozidrain G** drainage lattice provides additional interlocking and enhanced interface friction with cover soil material on steep slope installations. It has sufficient flow capacity in both long and cross direction to drain cover material and ensure slope stability. Shear box tests against site specific cover soil material and LLDPE geomembrane confirmed adequate **Pozidrain G** interface friction performance.

The project was finished on time and at optimum cost resulting in an area fit for a nature reserve.

The ABG Service

ABG proposed the system and provided design and site specific laboratory test results. Site support during the construction and timed deliveries ensured a successful construction.



Proving high friction as construction traffic spreads cover soil whilst protecting the geomembrane



Pozi G with drainage in all directions placed on top of 1mm LLDPE textured liner with



Finished, permanently stable, aesthetically pleasing green slope

Contact ABG today to discuss your project specific requirements and discover how ABG past experience and innovative products can help on your project.